

COMPANY IDENTITY: T C I Products Company  
 PRODUCT IDENTITY: DR61 ENAMEL REDUCER - SLOW DRY  
 SDS NUMBER: DR61

SDS DATE: 01/27/2014  
 ORIGINAL: 01/27/2014

## SAFETY DATA SHEET

This Safety Data Sheet conforms to ANSI Z400.5, and to the format requirements and the International Chemical Safety Cards of the Global Harmonizing System.

THIS SDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD)

IMPORTANT: Read this SDS before handling & disposing of this product.

Pass this information on to employees, customers, & users of this product.

### SECTION 1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER

PRODUCT IDENTITY: DR61 ENAMEL REDUCER - SLOW DRY  
 PRODUCT USES: Enamel Reducer

COMPANY IDENTITY: T C I Products Company  
 COMPANY ADDRESS: 420 E Desoto  
 COMPANY CITY: St. Louis, MO 63147  
 COMPANY PHONE: 1-314-231-3075  
 EMERGENCY PHONES: CHEMTREC: 1-800-424-9300 (USA)  
 CANUTEC: 1-613-996-6666 (CANADA)



### SECTION 2. HAZARDS IDENTIFICATION

**DANGER!!**

**EXPOSURE PREVENTION: STRICT HYGIENE!**  
**AVOID EXPOSURE OF (PREGNANT) WOMEN, ADOLESCENTS, CHILDREN!**

#### 2.1 HAZARD STATEMENTS: (CAT = Hazard Category)

H100s = General, H200s = Physical, H300s = Health, H400s = Environmental

H225 Highly flammable liquid and vapor.(CAT:2)  
 H304 May be fatal if swallowed and enters airways.(CAT:1)  
 H315 Causes skin irritation.(CAT:2)  
 H320 Causes eye irritation.(CAT:2)  
 H332 Harmful if inhaled.(CAT:4)  
 H335 May cause respiratory irritation.(CAT:3)  
 H336 May cause drowsiness or dizziness.(CAT:3)  
 H371 May cause damage to organs.(CAT:2)

#### 2.2 PRECAUTIONARY STATEMENTS:

P100s = General, P200s = Prevention, P300s = Response, P400s = Storage, P500s = Disposal

P260 Do not breathe dust/fume/gas/mist/vapors/spray.  
 P264 Wash with soap & water thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P302+352 IF ON SKIN: Wash with soap & water.  
 P304+340 IF INHALED: Remove victim to fresh air & keep at rest in a position comfortable for breathing.  
 P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present & easy to do - Continue rinsing.  
 P309+311 If exposed or you feel unwell: Call a POISON CENTER or doctor/physician.  
 P332+313 If skin irritation occurs: Get medical advice/attention.  
 P337+313 If eye irritation persists, get medical advice/attention.  
 P361 Remove/Take off immediately all contaminated clothing.  
 P363 Wash contaminated clothing before reuse.  
 P405 Store locked up.  
 P501 Dispose of contents/container to an approved waste disposal plant.

SEE SECTIONS 8, 11 & 12 FOR TOXICOLOGICAL INFORMATION.

COMPANY IDENTITY: T C I Products Company  
 PRODUCT IDENTITY: DR61 ENAMEL REDUCER - SLOW DRY  
 SDS NUMBER: DR61

SDS DATE: 01/27/2014  
 ORIGINAL: 01/27/2014

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MATERIAL	CAS#	EINECS#	WT %
Toluene	108-88-3	203-625-9	25-35
Light Aliphatic Naphtha	*64742-89-8	-	25-35
2-Butoxyethanol	111-76-2	203-905-0	10-20
Acetone	67-64-1	200-662-2	5-15
Xylenes	1330-20-7	215-535-7	0- 5
Methanol	67-56-1	200-659-6	0- 5
Ethylbenzene	100-41-4	202-849-4	0- 5

TRACE COMPONENTS: Trace ingredients (if any) are present in < 1% concentration, (< 0.1% for potential carcinogens, reproductive toxins, respiratory tract mutagens, and sensitizers). None of the trace ingredients contribute significant additional hazards at the concentrations that may be present in this product. All pertinent hazard information has been provided in this document, per the requirements of the Federal Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State equivalents, and Canadian Hazardous Materials Identification System Standard (CPR 4).

### SECTION 4. FIRST AID MEASURES

#### 4.1 GENERAL ADVICE:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists, refer to Section 8 for specific personal protective equipment.

#### 4.2 EYE CONTACT:

If this product enters the eyes, open eyes while under gently running water. Use sufficient force to open eyelids. "Roll" eyes to expose more surface. Minimum flushing is for 15 minutes. Seek immediate medical attention.

#### 4.3 SKIN CONTACT:

If the product contaminates the skin, immediately begin decontamination with running water. Minimum flushing is for 15 minutes. Remove contaminated clothing, taking care not to contaminate eyes. If skin becomes irritated and irritation persists, medical attention may be necessary. Wash contaminated clothing before reuse, discard contaminated shoes.

#### 4.4 INHALATION:

After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, trained personnel should immediately begin artificial respiration. If the heart has stopped, trained personnel should immediately begin cardiopulmonary resuscitation (CPR). Seek immediate medical attention.

#### 4.5 SWALLOWING:

If swallowed, CALL PHYSICIAN OR POISON CONTROL CENTER FOR MOST CURRENT INFORMATION. If professional advice is not available, give two glasses of water to drink. DO NOT INDUCE VOMITING. Never induce vomiting or give liquids to someone who is unconscious, having convulsions, or unable to swallow. Seek immediate medical attention.

#### 4.6 NOTES TO PHYSICIAN:

There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. Any material aspirated during vomiting may cause lung injury. Therefore, emesis should not be induced mechanically or pharmacologically. If it is considered necessary to evacuate the stomach contents, this should be done by means least likely to cause aspiration (such as: Gastric lavage after endotracheal intubation).

### SECTION 5. FIRE FIGHTING MEASURES

#### 5.1 FIRE & EXPLOSION PREVENTIVE MEASURES

NO open flames, NO sparks, & NO smoking. Above flash point, use a closed system, ventilation, explosion-proof electrical equipment, lighting. Do NOT use compressed air for filling, discharging, or handling.

COMPANY IDENTITY: T C I Products Company  
PRODUCT IDENTITY: DR61 ENAMEL REDUCER - SLOW DRY  
SDS NUMBER: DR61

SDS DATE: 01/27/2014  
ORIGINAL: 01/27/2014

## SECTION 5. FIRE FIGHTING MEASURES (CONTINUED)

### 5.2 EXTINGUISHING MEDIA

Use dry powder, AFFF, alcohol-resistant foam, water spray, water in large amounts, carbon dioxide.

### 5.3 SPECIAL FIRE FIGHTING PROCEDURES

Water spray may be ineffective on fire but can protect fire-fighters & cool closed containers. Use fog nozzles if water is used. Do not enter confined fire-space without full bunker gear. (Helmet with face shield, bunker coats, gloves & rubber boots).

### 5.4 UNUSUAL EXPLOSION AND FIRE PROCEDURES

**EXTREMELY FLAMMABLE!! VAPORS CAN CAUSE FLASH FIRE**  
Isolate from oxidizers, heat, sparks, electric equipment & open flame. Closed containers may explode if exposed to extreme heat. Applying to hot surfaces requires special precautions. Empty container very hazardous! Continue all label precautions!

## SECTION 6. ACCIDENTAL RELEASE MEASURES

### 6.1 SPILL AND LEAK RESPONSE AND ENVIRONMENTAL PRECAUTIONS:

Uncontrolled releases should be responded to by trained personnel using pre-planned procedures. Proper protective equipment should be used. In case of a spill, clear the affected area, protect people, and respond with trained personnel. ELIMINATE all ignition sources (no smoking, flares, sparks, or flames in immediate area).

### 6.2 PERSONAL PROTECTIVE EQUIPMENT

The proper personal protective equipment for incidental releases (such as: 1 Liter of the product released in a well-ventilated area), use impermeable gloves, they should be Level B: **triple-gloves (rubber gloves and nitrile gloves over latex gloves), chemical resistant suit and boots, hard-hat, and Self-Contained Breathing Apparatus** specific for the material handled, goggles, face shield, and appropriate body protection. In the event of a large release, use impermeable gloves, specific for the material handled, chemically resistant suit and boots, and hard hat. Self-Contained Breathing Apparatus or respirator may be required where engineering controls are not adequate or conditions for potential exposure exist. When respirators are required, select NIOSH/MSHA approved based on actual or potential airborne concentrations in accordance with latest OSHA and/or ANSI recommendations.

### 6.3 ENVIRONMENTAL PRECAUTIONS:

Stop spill at source. Construct temporary dikes of dirt, sand, or any appropriate readily available material to prevent spreading of the material. Close or cap valves and/or block or plug hole in leaking container and transfer to another container. Keep from entering storm sewers and ditches which lead to waterways, and if necessary, call the local fire or police department for immediate emergency assistance.

### 6.4 CONTAINMENT AND CLEAN-UP MEASURES:

Absorb spilled liquid with polypads or other suitable absorbent materials. If necessary, neutralize using suitable buffering material, (acid with soda ash or base with phosphoric acid), and test area with litmus paper to confirm neutralization. Clean up with non-combustible absorbent (such as: sand, soil, and so on). Shovel up and place all spill residue in suitable containers. Dispose of at an appropriate waste disposal facility according to current applicable laws and regulations and product characteristics at time of disposal (see Section 13 - Disposal Considerations).

COMPANY IDENTITY: T C I Products Company  
PRODUCT IDENTITY: DR61 ENAMEL REDUCER - SLOW DRY  
SDS NUMBER: DR61

SDS DATE: 01/27/2014  
ORIGINAL: 01/27/2014

## SECTION 7. HANDLING AND STORAGE

### 7.1 HANDLING

Put on appropriate personal protective equipment (See Section 8). Eating, drinking, and smoking should be prohibited in areas where this material is handled, stored, and processed. Workers should wash hands and face before eating, drinking, smoking and using the toilet facilities. Do not breathe vapor or mist. Do not swallow. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container. Isolate from oxidizers, heat, & open flame. Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear goggles, face shield, gloves, apron & footwear impervious to material. Wash clothing before reuse. Avoid free fall of liquid. Ground containers when transferring. Do not flame cut, braze, or weld. Empty container very hazardous! Continue all label precautions!

### 7.2 STORAGE

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (See Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Inspect all incoming containers before storage to ensure containers are properly labeled and not damaged.

### 7.3 NONBULK: CONTAINERS:

Store containers in a cool, dry location, away from direct sunlight, sources of intense heat, or where freezing is possible. Material should be stored in secondary containers or in a diked area, as appropriate. Store containers away from incompatible chemicals (see Section 10, Stability and Reactivity). Post warning and "NO SMOKING" signs in storage and use areas, as appropriate. Empty containers should be handled with care. Never store food, feed, or drinking water in containers which held this product.

### 7.4 BULK CONTAINERS:

All tanks and pipelines which contain this material must be labeled. Perform routine maintenance on tanks or pipelines which contain this product. Report all leaks immediately to the proper personnel.

### 7.5 TANK CAR SHIPMENTS:

Tank cars carrying this product should be loaded and unloaded in strict accordance with tank-car manufacturer's recommendation and all established on-site safety procedures. Appropriate personal protective equipment must be used (see Section 8, Engineering Controls and Personal Protective Equipment.). All loading and unloading equipment must be inspected, prior to each use. Loading and unloading operations must be attended, at all times. Tank cars must be level, brakes must be set or wheels must be locked or blocked prior to loading or unloading. Tank car (for loading) or storage tanks (for unloading) must be verified to be correct for receiving this product and be properly prepared, prior to starting the transfer operations. Hoses must be verified to be in the correct positions, before starting transfer operations. A sample (if required) must be taken and verified (if required) prior to starting transfer operations. All lines must be blown-down and purged before disconnecting them from the tank car or vessel.

### 7.6 PROTECTIVE PRACTICES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT:

Follow practices indicated in Section 6 (Accidental Release Measures). Make certain application equipment is locked and tagged-out safely. Always use this product in areas where adequate ventilation is provided. Collect all rinsates and dispose of according to applicable Federal, State, Provincial, or local procedures.

COMPANY IDENTITY: T C I Products Company  
 PRODUCT IDENTITY: DR61 ENAMEL REDUCER - SLOW DRY  
 SDS NUMBER: DR61

SDS DATE: 01/27/2014  
 ORIGINAL: 01/27/2014

### SECTION 7. HANDLING AND STORAGE (CONTINUED)

#### 7.7 EMPTY CONTAINER WARNING:

Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. **DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY BURST AND CAUSE INJURY OR DEATH.**

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

MATERIAL	CAS#	EINECS#	TWA (OSHA)	TLV (ACGIH)
Toluene	108-88-3	203-625-9	200 ppm	50 ppm A4
Light Aliphatic Naphtha	*64742-89-8	-	500 ppm	300 ppm
2-Butoxyethanol	111-76-2	203-905-0	50 ppm S	20 ppm S
Acetone	67-64-1	200-662-2	1000 ppm	500 ppm A4
Xylenes	1330-20-7	215-535-7	100 ppm	100 ppm A4
Methanol	67-56-1	200-659-6	200 ppm S	200 ppm S
Ethylbenzene	100-41-4	202-849-4	100 ppm	100 ppm A3

MATERIAL	CAS#	EINECS#	CEILING	STEL(OSHA/ACGIH)	HAP
Toluene	108-88-3	203-625-9	None Known	None Known	Yes
Light Aliphatic Naphtha	*64742-89-8	-	None Known	5.3E3 ppm	No
Acetone	67-64-1	200-662-2	None Known	750 ppm	No
Xylenes	1330-20-7	215-535-7	None Known	150 ppm	Yes
Methanol	67-56-1	200-659-6	None Known	250 ppm	Yes
Ethylbenzene	100-41-4	202-849-4	None Known	125 ppm	Yes

In addition, using manufacturers' data, based on EPA Method 311, the following EPA Hazardous Air Pollutants may be present in trace amounts (less than 0.1%): Benzene, Cumene

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION (CONTINUED)

#### 8.1 RESPIRATORY EXPOSURE CONTROLS

Maintain airborne contaminant concentrations below exposure limits given above. If respiratory protection is needed, use only protection authorized in 29 CFR 1910.134, European Standard EN 149, or applicable State regulations. If adequate ventilation is not available or there is potential for airborne exposure above the exposure limits, a respirator may be worn up to the respirator exposure limitations, check with respirator equipment manufacturer's recommendations/limitations. For a higher level of protection, use positive pressure supplied air respiration protection or Self-Contained Breathing Apparatus or if oxygen levels are below 19.5% or are unknown.

#### 8.2 EMERGENCY OR PLANNED ENTRY INTO UNKNOWN CONCENTRATIONS OR IDLH CONDITIONS

Positive pressure, full-face piece Self-Contained Breathing Apparatus; or positive pressure, full-face piece Self-Contained Breathing Apparatus with an auxiliary positive pressure Self-Contained Breathing Apparatus.

#### 8.3 VENTILATION

LOCAL EXHAUST: Necessary                      MECHANICAL (GENERAL): Necessary  
 SPECIAL: None                                      OTHER: None  
 Please refer to ACGIH document, "Industrial Ventilation, A Manual of Recommended Practices", most recent edition, for details.

#### 8.4 EYE PROTECTION:

Splash goggles or safety glasses. Face-shields are recommended when the operation can generate splashes, sprays or mists.

COMPANY IDENTITY: T C I Products Company  
 PRODUCT IDENTITY: DR61 ENAMEL REDUCER - SLOW DRY  
 SDS NUMBER: DR61

SDS DATE: 01/27/2014  
 ORIGINAL: 01/27/2014

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION (CONTINUED)

### 8.5 HAND PROTECTION:

Use gloves chemically resistant to this material. Preferred examples: Butyl rubber, Chlorinated Polyethylene, Polyethylene, Ethyl vinyl alcohol laminate ("EVAL"), Polyvinyl alcohol ("PVA"). Examples of acceptable glove barrier materials include: Natural rubber ("latex"), Neoprene, Nitrile/butadiene rubber ("nitrile") or ("NBR"), Polyvinyl chloride ("PVC") or "vinyl", Viton. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

### 8.6 BODY PROTECTION:

Use body protection appropriate for task. Cover-all, rubber aprons, or chemical protective clothing made from impervious materials are generally acceptable, depending on the task.

### 8.7 WORK & HYGIENIC PRACTICES:

Provide readily accessible eye wash stations & safety showers. Wash at end of each shift & before eating, smoking or using the toilet. Remove clothing that becomes contaminated. Destroy contaminated leather articles. Launder or discard contaminated clothing.

## SECTION 9. PHYSICAL & CHEMICAL PROPERTIES

APPEARANCE:	Liquid, Water-White
ODOR:	Ketone
ODOR THRESHOLD:	Not Available
pH (Neutrality):	Not Available
MELTING POINT/FREEZING POINT:	Not Available
BOILING RANGE (IBP,50%,Dry Point):	58 122 172 C / 137 252 342 F
FLASH POINT (TEST METHOD):	-16 C / 2 F (TCC) (Lowest Component)
EVAPORATION RATE (n-Butyl Acetate=1):	0.558
FLAMMABILITY CLASSIFICATION:	Class I B
LOWER FLAMMABLE LIMIT IN AIR (% by vol):	1.6
UPPER FLAMMABLE LIMIT IN AIR (% by vol):	Not Available
VAPOR PRESSURE (mm of Hg)@20 C	54.9
VAPOR DENSITY (air=1):	3.1
GRAVITY @ 68/68 F / 20/20 C:	
DENSITY:	0.821
SPECIFIC GRAVITY (Water=1):	0.823
POUNDS/GALLON:	6.853
WATER SOLUBILITY:	Appreciable
PARTITION COEFFICIENT (n-Octane/Water):	Not Available
AUTO IGNITION TEMPERATURE:	287 C / 550 F
DECOMPOSITION TEMPERATURE:	Not Available
VOCs (>0.044 Lbs/Sq In) :	84.1 Vol% / 691.9 g/L / 5.7 Lbs/Gal
TOTAL VOC'S (TVOC)*:	100.0 Vol% / 822.7 g/L / 6.8 Lbs/Gal
NONEXEMPT VOC'S (CVOC)*:	86.5 Vol% / 715.8 g/L / 5.9 Lbs/Gal
HAZARDOUS AIR POLLUTANTS (HAPS):	40.7 Wt% / 334.6 g/L / 2.7 Lbs/Gal
NONEXEMPT VOC PARTIAL PRESSURE (mm of Hg @ 20 C)	0.0
VISCOSITY @ 20 C (ASTM D445):	Not Available

\* Using CARB (California Air Resources Board Rules).

COMPANY IDENTITY: T C I Products Company  
PRODUCT IDENTITY: DR61 ENAMEL REDUCER - SLOW DRY  
SDS NUMBER: DR61

SDS DATE: 01/27/2014  
ORIGINAL: 01/27/2014

## SECTION 10. STABILITY & REACTIVITY

### 10.1 STABILITY

Stable under normal conditions.

### 10.2 CONDITIONS TO AVOID

Isolate from oxidizers, heat, sparks, electric equipment & open flame.

### 10.3 MATERIALS TO AVOID

Reacts violently with strong oxidants, strong acids,  
causing fire & explosion hazard. Attacks many plastics, coatings.

### 10.4 HAZARDOUS DECOMPOSITION PRODUCTS

Carbon Monoxide, Carbon Dioxide from burning.

### 10.5 HAZARDOUS POLYMERIZATION

Will not occur.

## SECTION 11. TOXICOLOGICAL INFORMATION

### 11.1 ACUTE HAZARDS

#### 11.11 EYE & SKIN CONTACT:

Primary irritation to skin, defatting, dermatitis.  
Absorption thru skin increases exposure.  
Primary irritation to eyes, redness, tearing, blurred vision.  
Liquid can cause eye irritation. Wash thoroughly after handling.

#### 11.12 INHALATION:

Anesthetic. Irritates respiratory tract. Acute overexposure  
can cause serious nervous system depression. Vapor harmful.  
Breathing vapor can cause irritation.  
Acute overexposure can cause harm to affected organs by routes of entry.  
Use of alcoholic beverages enhances the harmful effect.

#### 11.13 SWALLOWING:

Harmful or fatal if swallowed.  
Swallowing can cause abdominal irritation, nausea, vomiting & diarrhea.  
The symptoms of chemical pneumonitis may not show up for a few days.

### 11.2 SUBCHRONIC HAZARDS/CONDITIONS AGGRAVATED

#### CONDITIONS AGGRAVATED

Chronic overexposure can cause harm to affected organs by routes of entry.  
Persons with severe skin, liver or kidney problems should avoid use.

### 11.3 CHRONIC HAZARDS

#### 11.31 CANCER, REPRODUCTIVE & OTHER CHRONIC HAZARDS:

Pregnant women should avoid use. May cause birth defects.  
Liver tumors have been reported in laboratory mice.  
Overexposure may create cancer risk.  
Leukemia been reported in humans from Benzene.  
This product contains less than 135 ppm of Benzene.  
Not considered hazardous in such low concentrations.  
Absorption thru skin may be harmful. Studies with laboratory animals indicate this  
product can cause damage to fetus.  
Depending on degree of exposure, periodic medical examination is indicated.  
Some persons may be more sensitive to the substance's effect on blood cells.

COMPANY IDENTITY: T C I Products Company  
 PRODUCT IDENTITY: DR61 ENAMEL REDUCER - SLOW DRY  
 SDS NUMBER: DR61

SDS DATE: 01/27/2014  
 ORIGINAL: 01/27/2014

#### SECTION 11. TOXICOLOGICAL INFORMATION (CONTINUED)

- 11.32 IRRITANCY OF PRODUCT: This product is irritating to contaminated tissue.
- 11.33 SENSITIZATION TO THE PRODUCT: No component of this product is known as a sensitizer.
- 11.34 MUTAGENICITY: No known reports of mutagenic effects in humans.
- 11.35 EMBRYOTOXICITY: No known reports of embryotoxic effects in humans.
- 11.36 TERATOGENICITY: No known reports of teratogenic effects in humans.
- 11.37 REPRODUCTIVE TOXICITY: No known reports of reproductive effects in humans.

A mutagen is a chemical which causes permanent changes to genetic material (DNA) such that the changes will propagate through generational lines. An embryotoxin is a chemical which causes damage to a developing embryo (such as: within the eight weeks of pregnancy in humans), but the damage does not propagate across generational lines. A teratogen is a chemical which causes damage to a developing fetus, but the damage does not propagate across generational lines. A reproductive toxin is any substance which interferes in any way with the reproductive process.

#### 11.4 MAMMALIAN TOXICITY INFORMATION

MATERIAL	CAS#	EINECS#	LOWEST KNOWN LETHAL DOSE DATA
Ethylene Glycol Butyl Ether	111-76-2	203-905-0	LOWEST KNOWN LD50 (ORAL) 320.0 mg/kg(Rabbits)
Ethylene Glycol Butyl Ether	111-76-2	203-905-0	LOWEST KNOWN LC50 (VAPORS) 700 ppm (Mice)
Ethylene Glycol Butyl Ether	111-76-2	203-905-0	LOWEST KNOWN LD50 (SKIN) 440.0 mg/kg (Rabbits)

#### SECTION 12. ECOLOGICAL INFORMATION

- 12.1 ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.
- 12.2 EFFECT OF MATERIAL ON PLANTS AND ANIMALS:  
 This product may be harmful or fatal to plant and animal life if released into the environment. Refer to Section 11 (Toxicological Information) for further data on the effects of this product's components on test animals.
- 12.3 EFFECT OF MATERIAL ON AQUATIC LIFE:  
 The most sensitive known aquatic group to any component of this product is: Goldfish 250 ppm or mg/L (24 hour exposure). Keep out of sewers and natural water supplies. The substance is toxic to aquatic organisms.
- 12.4 MOBILITY IN SOIL  
 This material is a mobile liquid.
- 12.5 DEGRADABILITY  
 This product is partially biodegradable.
- 12.6 ACCUMULATION  
 This product does not accumulate or biomagnify in the environment.



COMPANY IDENTITY: T C I Products Company  
 PRODUCT IDENTITY: DR61 ENAMEL REDUCER - SLOW DRY  
 SDS NUMBER: DR61

SDS DATE: 01/27/2014  
 ORIGINAL: 01/27/2014

### SECTION 13. DISPOSAL CONSIDERATIONS

The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers and liners may retain some product residues. Vapor from some product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Processing, use or contamination may change the waste disposal requirements. Do not dispose of on land, in surface waters, or in storm drains. Waste should be recycled or disposed of in accordance with regulations. Large amounts should be collected for reuse or consigned to licensed hazardous waste haulers for disposal. ALL DISPOSAL MUST BE IN ACCORDANCE WITH ALL FEDERAL, STATE, PROVINCIAL, AND LOCAL REGULATIONS. IF IN DOUBT, CONTACT PROPER AGENCIES. EPA CHARACTERISTIC: D001

### SECTION 14. TRANSPORT INFORMATION

IF > 2626 LB / 1193 KG OF THIS PRODUCT IS IN 1 CONTAINER, IT EXCEEDS THE RQ OF XYLENES. "RQ" MUST BE PUT BEFORE THE DOT SHIPPING NAME.

MARINE POLLUTANT: No  
 DOT/TDG SHIP NAME: UN1263, Paint Related Material  
 (Contains: Toluene, Xylene), 3, PG-II  
 (FLAMMABLE LIQUID)  
 DRUM LABEL:  
 IATA / ICAO: UN1263, Paint Related Material  
 (Contains: Toluene, Xylene), 3, PG-II  
 IMO / IMDG: UN1263, Paint Related Material  
 (Contains: Toluene, Xylene), 3, PG-II  
 EMERGENCY RESPONSE GUIDEBOOK NUMBER: 128

### SECTION 15. REGULATORY INFORMATION

#### 15.1 EPA REGULATION:

SARA SECTION 311/312 HAZARDS: Acute Health, Chronic Health, Fire

All components of this product are on the TSCA list.

#### SARA Title III Section 313 Supplier Notification

This product contains the indicated <\*> toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right-To-Know Act of 1986 & of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material.

SARA TITLE III INGREDIENTS	CAS#	EINECS#	WT%	(REG. SECTION)	RQ(LBS)
*Toluene	108-88-3	203-625-9	25-35	(311,312,313,RCRA)	1000
*2-Butoxyethanol	111-76-2	203-905-0	10-20	(313)	None
Acetone	67-64-1	200-662-2	5-15	(311,312)	5000
*Xylenes	1330-20-7	215-535-7	0- 5	(311,312,313,RCRA)	100
*Methanol	67-56-1	200-659-6	0- 5	(311,312,313,RCRA)	5000
*Ethylbenzene	100-41-4	202-849-4	0- 5	(311,312,313,RCRA)	1000



COMPANY IDENTITY: T C I Products Company  
PRODUCT IDENTITY: DR61 ENAMEL REDUCER - SLOW DRY  
SDS NUMBER: DR61

SDS DATE: 01/27/2014  
ORIGINAL: 01/27/2014

**SECTION 15. REGULATORY INFORMATION (CONTINUED)**

Any release equal to or exceeding the RQ must be reported to the National Response Center (800-424-8802) and appropriate state and local regulatory agencies as described in 40 CFR 302.6 and 40 CFR 355.40 respectively. Failure to report may result in substantial civil and criminal penalties. State & local regulations may be more restrictive than federal regulations.

**15.2 STATE REGULATIONS:**

**CALIFORNIA SAFE DRINKING WATER & TOXIC ENFORCEMENT ACT (PROPOSITION 65):**

This product contains the following chemical known to the State of California to cause cancer: Ethylbenzene

This product contains the following chemicals known to the State of California to cause reproductive toxicity: Toluene, Methanol

**15.3 INTERNATIONAL REGULATIONS**

The identified components of this product are listed on the chemical inventories of the following countries:

Australia (AICS), Canada (DSL or NDSL), China (IECSC), Europe (EINECS, ELINCS), Japan (METI/CSCL, MHLW/ISHL), South Korea (KECI), New Zealand (NZIoC), Philippines (PICCS), Switzerland (SWISS), Taiwan (NECSI), USA (TSCA).

**15.4 CANADA: WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)**

B2: Flammable Liquid.

D2A: Contains a substance known to cause serious chronic toxicity or death.  
Ethylbenzene

D2B: Irritating to eyes/skin.

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all information required by the CPR.

**SECTION 16. OTHER INFORMATION**

**16.1 HAZARD RATINGS:**

HEALTH (NFPA): 2, HEALTH (HMIS): 2, FLAMMABILITY: 3, PHYSICAL HAZARD: 0  
(Personal Protection Rating to be supplied by user based on use conditions.)

This information is intended solely for the use of individuals trained in the NFPA & HMIS hazard rating systems.

**16.2 EMPLOYEE TRAINING**

See Section 2 for Risk & Safety Statements. Employees should be made aware of all hazards of this material (as stated in this SDS) before handling it.

**16.3 SDS DATE: 01/27/2014**

**NOTICE**

The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency.

Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon information contained herein.

This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.

Unless updated, the Safety Data Sheet is valid until 01/27/2017.